

CABLE REEL RACK

STANDARD STARTER UNITS

PART NO.	WIDTH	DEPTH	HEIGHT	WEIGHT	ROD CAPACITY PER LEVEL
CR2424096	24"	24"	96"	125.87	2280#
CR3624096	36"	24"	96"	140.19	1520#
CR4824096	48"	24"	96"	154.62	1060#
CR2436096	24"	36"	96"	130.26	2280#
CR3636096	36"	36"	96"	144.58	1520#
CR4836096	48"	36"	96"	159.01	1060#

Includes (2) uprights, (3) beams, (3) axle rods, (3) sets of axle brackets.

CR2424120	24"	24"	120"	160.66	2280#
CR3624120	36"	24"	120"	179.76	1520#
CR4824120	48"	24"	120"	199.00	1060#
CR2436120	24"	36"	120"	163.44	2280#
CR3636120	36"	36"	120"	182.54	1520#
CR4836120	48"	36"	120"	201.78	1060#

Includes (2) uprights, (4) beams, (4) axle rods, (4) sets of axle brackets.

CR2424144	24"	24"	144"	179.75	2280#
CR3624144	36"	24"	144"	197.66	1520#
CR4824144	48"	24"	144"	216.90	1060#
CR2436144	24"	36"	144"	183.56	2280#
CR3636144	36"	36"	144"	202.66	1520#
CR4836144	48"	36"	144"	221.90	1060#

Includes (2) uprights, (4) beams, (4) axle rods, (4) sets of axle brackets.

STANDARD ADDER UNITS

PART NO.	WIDTH	DEPTH	HEIGHT	WEIGHT	ROD CAPACITY PER LEVEL
CR2424096A	24"	24"	96"	84.77	2280#
CR3624096A	36"	24"	96"	99.09	1520#
CR4824096A	48"	24"	96"	113.52	1060#
CR2436096A	24"	36"	96"	86.96	2280#
CR3636096A	36"	36"	96"	101.28	1520#
CR4836096A	48"	36"	96"	115.71	1060#

Includes (1) upright, (3) beams, (3) axle rods, (3) sets of axle brackets.

CR2424120A	24"	24"	120"	109.44	2280#
CR3624120A	36"	24"	120"	128.54	1520#
CR4824120A	48"	24"	120"	147.78	1060#
CR2436120A	24"	36"	120"	110.83	2280#
CR3636120A	36"	36"	120"	129.93	1520#
CR4836120A	48"	36"	120"	149.17	1060#

Includes (1) upright, (4) beams, (4) axle rods, (4) sets of axle brackets.

CR2424144A	24"	24"	144"	118.39	2280#
CR3624144A	36"	24"	144"	137.49	1520#
CR4824144A	48"	24"	144"	156.73	1060#
CR2436144A	24"	36"	144"	120.89	2280#
CR3636144A	36"	36"	144"	139.98	1520#
CR4836144A	48"	36"	144"	159.23	1060#

Includes (1) upright, (4) beams, (4) axle rods, (4) sets of axle brackets.



HUSKY
RACK & WIRE™



AXLE BRACKETS

PART NO.	WEIGHT
I4500	3#/Pair

Cut size for axle is 1/2" less than actual width.
Example 24" wide unit - use 23-1/2" axles.
Max. rod diameter 1 5/8".