

CABLE REEL



www.huskyrackandwire.com

6146 Denver Industrial Park Circle • Denver, NC 28037
 Phone 704-483-1900 • Fax 704-483-1911
productinfo@huskyrackandwire.com

STANDARD STARTER UNITS

| Part No. | Width | Depth | Height | Weight |
|--------------|-------|-------|--------|--------|
| CR-24-24-96 | 24" | 24" | 96" | 125.87 |
| CR-36-24-96 | 36" | 24" | 96" | 140.19 |
| CR-48-24-96 | 48" | 24" | 96" | 154.62 |
| CR-24-36-96 | 24" | 36" | 96" | 130.26 |
| CR-36-36-96 | 36" | 36" | 96" | 144.58 |
| CR-48-36-96 | 48" | 36" | 96" | 159.01 |
| CR-24-24-120 | 24" | 24" | 120" | 160.66 |
| CR-36-24-120 | 36" | 24" | 120" | 179.76 |
| CR-48-24-120 | 48" | 24" | 120" | 199.00 |
| CR-24-36-120 | 24" | 36" | 120" | 163.44 |
| CR-36-36-120 | 36" | 36" | 120" | 182.54 |
| CR-48-36-120 | 48" | 36" | 120" | 201.78 |
| CR-24-24-144 | 24" | 24" | 144" | 179.75 |
| CR-36-24-144 | 36" | 24" | 144" | 197.66 |
| CR-48-24-144 | 48" | 24" | 144" | 216.90 |
| CR-24-36-144 | 24" | 36" | 144" | 183.56 |
| CR-36-36-144 | 36" | 36" | 144" | 202.66 |
| CR-48-36-144 | 48" | 36" | 144" | 221.90 |

Green Uprights and Orange Beams

Standard Starter Units

8' units include:

2 uprights, 3 tie beams, 3 axle rods, 3 sets of axle brackets

10' & 12' units include:

2 uprights, 4 tie beams, 4 axle rods, 4 sets of axle brackets

STANDARD ADDER UNITS

| Part No. | Width | Depth | Height | Weight |
|---------------|-------|-------|--------|--------|
| CR-24-24-96A | 24" | 24" | 96" | 84.77 |
| CR-36-24-96A | 36" | 24" | 96" | 99.09 |
| CR-48-24-96A | 48" | 24" | 96" | 113.52 |
| CR-24-36-96A | 24" | 36" | 96" | 86.96 |
| CR-36-36-96A | 36" | 36" | 96" | 101.28 |
| CR-48-36-96A | 48" | 36" | 96" | 115.71 |
| CR-24-24-120A | 24" | 24" | 120" | 109.44 |
| CR-36-24-120A | 36" | 24" | 120" | 128.54 |
| CR-48-24-120A | 48" | 24" | 120" | 147.78 |
| CR-24-36-120A | 24" | 36" | 120" | 110.83 |
| CR-36-36-120A | 36" | 36" | 120" | 129.93 |
| CR-48-36-120A | 48" | 36" | 120" | 149.17 |
| CR-24-24-144A | 24" | 24" | 144" | 118.39 |
| CR-36-24-144A | 36" | 24" | 144" | 137.49 |
| CR-48-24-144A | 48" | 24" | 144" | 156.73 |
| CR-24-36-144A | 24" | 36" | 144" | 120.89 |
| CR-36-36-144A | 36" | 36" | 144" | 139.98 |
| CR-48-36-144A | 48" | 36" | 144" | 159.23 |

Standard Adder Units

8' units include:

1 upright, 3 tie beams, 3 axle rods, 3 sets of axle brackets

10' & 12' units include:

1 upright, 4 tie beams, 4 axle rods, 4 sets of axle brackets

AXLE BRACKETS

| Part No. | Capacity | Weight |
|----------|------------|---------|
| I4500 | 2000#/Pair | 3#/Pair |

Width dimensions between columns - net axle brackets. Cut size for axle is 1/2" less than actual width. Example 24" wide unit - use 23-1/2" axles. Max. rod diameter 1 5/8".